

PF315V+



Key Features:

- Fanless iCore Performance
- Perfect Flat, Bezel-Free Pure Glass Multi-Touch Screen
- Spill & Dust Resistant, Rugged & Robust Design, Die Cast Aluminum Housing
- Supports Dual HDD and RAID Function
- Supports 2nd Rear Display

Specifications			
	Part No.	PF315V+ Atom Fanless	PF315V+ iCore Fanless
System	CPU Support	Intel® Pineview-D Atom D525 1.8 GHz	Intel® IvyBridge iCore i3 or i5 FANLESS
	Memory	SODIMM DDR3/2Gb RAM standard, up to 4GB	
Storage	HDD or SSD	2.5" SATA HDD or SSD with RAID 0 / 1 option	
I/O Ports	Parallel Port	1 x LPT Port	
	Serial Ports	4 x DB-9 COM ports (all with DC 5 / 12V output on Pin 9 selectable)	
	1 x RJ-45 COM port for VFD display	1 x 10 / 100 / 1000 Mbps Gigabit LAN	
	USB Ports	8 x USB 2.0 ports	
	LAN Port	1 x 10 / 100 / 1000 Mbps Gigabit LAN	
	Keyboard / Mouse Port	1 x PS/2 keyboard port	
	Audio Port	1 x Line in, 1 x Line out, 1 x MIC In	
	Cash Drawer	1 x RJ11 Cash Drawer port (12V/24V)	
	Speaker Output	2 x 1W Speaker	
	DC Output	1 x DC 12V Output for 2nd display	
Power	Power Supply	AC to DC 24V 120W external power supply	
	Indicator lights	4 x LED Indicator (Standby 5V / Power on / HDD / LAN Status)	
Physical Dimension (L x W x D)	System Size	360 x 360 x 255 mm (14 x 14 x 10)	
	Packaging	423 x 456 x 501 mm (16.5 x 18 x 20)	
	Weight	10.5 KG	
LCD Display & Touch Panel	Main Display	15" LCD Touch Monitor	
	Max. Resolution	1024 x 768 (Default)	
	Brightness	250 cd/m2	
	Touch Screen	Resistive or Projected Capacitive	
Options	2nd Display	8.4" VFD customer display or 15" 2nd LCD display	
	MSR	MSR + Biometric	
	Storage	RAID option available, HDD or SSD	
Safety & Environment	EMC & Safety	CE / FCC Certified	
	OS Compatibility	XP / Windows 7 / WEPOS / POSReady 2009	



Flat and seamless screen surface crafted to be water/dust resistant



Service-friendly front I/O ports



Patented design for superior serviceability



Robust aluminum die-cast shell



Easy access to hard drive

