

PF317V+



Key Features

- Fanless iCore Performance
- Perfect Flat, Bezel-Free Pure Glass Multi-Touch Screen
- Spill & Dust Resistant, Rugged & Robust Design, Die Cast Aluminum Housing
- Supports Dual HDD and RAID Function
- Supports 2nd Rear Display

Specifications		
System	CPU Support	Intel® IvyBridge iCore i3 or i5 FANLESS
	Memory	SODIMM DDR3/2Gb RAM standard, up to 16GB
Storage	HDD or SSD	2.5" SATA HDD or SSD with RAID 0 / 1 option
	Parallel Port	1 x LPT Port
I/O Ports	Serial Ports	4 x DB-9 COM ports 1; x RJ-45 COM port for VFD display (all with DC 5 / 12V output on Pin 9 selectable)
	USB Ports	8 x USB 2.0 ports
	LAN Port	1 x Gigabit LAN
	Keyboard / Mouse Port	1 x PS/2 keyboard port
	Audio Port	1 x Line in, 1 x Line out, 1 x MIC In
	Cash Drawer	1 x RJ11 Cash Drawer port (12V/24V)
	Speaker Output	2 x 1W Speaker
	DC Output	1 x DC 12V Output for 2nd display
Power	Power Supply	AC to DC 24V 120W external power supply
	Indicator lights	4 x LED Indicator (Standby 5V / Power on / HDD / LAN Status)
Physical Dimension (L x W x D)	System Size	360 x 360 x 255 mm (14 x 14 x 10)
	Packaging	423 x 456 x 501 mm (16.5 x 18 x 20)
	Weight	10.5 KG
LCD Display & Touch Panel	Main Display	17" LCD Touch Monitor
	Max. Resolution	1280 x 1024
	Brightness	250 cd/m2
Options	Touch Screen	Capacitive (PCT)
	2nd Display	VFD 8", 8.4", 10", 17", 19"
	MSR	3-Track STD MSR or MSR + Biometric
	Storage	RAID option available, HDD or SSD
Safety & Environment	EMC & Safety	CE / FCC Certified
	OS Compatibility	Windows 7 / POSReady 2009 / Windows 8.1



Flat and seamless screen surface crafted to be water/dust resistant



Service-friendly front I/O ports



Patented design for superior serviceability



Robust aluminum die-cast shell



Easy access to hard drive

