

# HPRT TP806



### Key Features:

- Jam-free cutter
- 300mm/s high printing speed
- Supports 2D, QR, matrix barcodes
- USB interface and choice of 2<sup>nd</sup> interface as serial, parallel, ethernet, WiFi or bluetooth



Specification		
PRINTING	METHOD	Direct Thermal
	SPEED	Max 300 mm/s
	RESOLUTION	203 dpi
MEMORY	RAM	1 Mb
	FLASH	4 Mb
PAPER	TYPE	Standard Thermal Paper
	WIDTH	79.5 ±0.5mm/57.5±0.5MM
	THICKNESS	0.056~0.1MM
	ROLL DIAMETER	Max. Ø 83mm
	LOADING	Easy loading
	CUTTING	Auto or Manual cutting
INTERFACE	DEFAULT	USB, Drawer
	OPTIONAL	RS232, Parallel, Ethernet, WiFi, Bluetooth
SOFTWARE	DRIVER	Windows 2000/XP/Vista/7/S/POSReady, Linux, OPOS
POWER SUPPLY	INPUT	AC100V-20V,50-60Hz
	OUTPUT	DC24V +5%, 2.0A, A-1009-3P interface
	CASH DRAWER CONTROL	DC 24V/IA
BARCODE	1D	UPC-A/UPC-E/EAN8 / EAN13 / CODE39/ ITF CODEBAR / CODE128 / CODE93
	2D	PDF417, QR code (DataMatrix/Maxicode/Aztec optional)
PHYSICAL CHARACTERISTICS	OPERATING	5~45°C / 10~95%RH
	DIMENSION	191 x 130 x 131 mm (LxWxH)
	NET WEIGHT	1.63 kg (without paper roll)
RELIABILITY	TPH LIFE	150 km
	CUTTER LIFE	2,000,000 times
FIRMWARE	EMULATION	ESC/POS



PWR + RJ11 + Serial + USB  
(Other options: Parallel, LAN, WiFi & Bluetooth)



Available in black or white

